



公差等级/General	tolerance/(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50			

ITEM	NAME OF PART	MATERIAL	NOTES
4	Screw	Steel	M3.5/Zn Plated
3	Cage	Brass	M3.5/Ni Plated
2	Pin header	Copper	Sn Plated
1	Housing	PA66	UL94V-0

UL 标准 /UL Standard:	B	C	D
额定电压/电涌 /Rated Voltage(V)/Current(A)	300/20	300/20	/
IEC 标准 /IEC Standard:	III/2		
过压类别 /Overvoltage Category /污秽等级 /Pollution Degree	III/2		
额定电压/电涌 /Rated Voltage(V)/Current(A)	750/32		
工频耐压 /Withstanding voltage	AC2000V/1min		
螺栓扭矩 /Torque Tightening(N·m/Lb·in)	M3.5: 0.8/7.08		
线芯范围 (硬线和软线) /Wire Range(rigid and flexible)(mm ² /AWG)	0.5~4/20~10		
间距 /Pitch(mm) /线芯范围 /Poles	7.5/N=01~02P		
剥线长度 /Stripping length(mm)	10~12		
使用温度范围 /Operating Temperature(°C)	-40~+105		
符合RoHS环保要求 /Conform to RoHS	Yes		
标准颜色编号 /Standard color number: RAL	RAL 2000		

MATERIAL: / SURFACE: /

MAT NO.: /

STATUS: /

APPD: /

CHKD: /

DRT: CenWZ 2020.05.19

SIZE: A4

NAME: **DEGSON** NINGBO DEGSON ELECTRICAL CO., LTD
宁波高松电子有限公司

TSC4-XXP-15-01A(H)

DRAWING NO.: TSC4-C02

TYPE: CUSTOMER DRAWING

REV	ECN	DESCRIPTION	DRT	DATE	REV	TO