


公差等级/General Tolerances(mm)		0.1/10	
0	>3	>10	>400
3	~6	~120	~500
6	10	180	400
10	30	250	500
±0.12	±0.18	±0.22	±0.26
	±0.31	±0.37	±0.57
	±0.80	±0.93	±1.05
	±1.15	±1.60	±2.20
	±2.50		
			±Z



5	Clapboard	PA66	UL94V-0
4	Spring	Stainless steel	/
3	Pin header	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	/	750/17	/
工频电压/Withstanding Voltage(V/1Min)		AC3000	
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	0.2~2.5/28~12		
间距/Pitch(mm)/线数范围/Poles	7.5/N=02~16P		
剥线长度/Stripping length(mm)	5~6		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS要求/Conform to RoHS	Yes		

MATERIAL: /

MAT NO.: /

STATUS: /

NAME: /

APPD: Li GL 2020.06.10

DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD

CHKD: MoEK 2020.06.10

DG245-7.5-XXP-1Y-00A(H)

DRT: WangW 2020.06.10

DRAWING NO.: DG245-7.5-C01

REV

ECN

DESCRIPTION

DRT

DATE

SIZE: A4

TYPE: CUSTOMER DRAWING

SCALE: 2:1

SHEET 1/1

D

C

B

A

1

2

3

4

5

6