



公差等级/General Tolerances(mm)		公差等级/General Tolerances(mm)										公差等级/General Tolerances(mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~
3	6	10	18	30	50	80	120	180	250	315	400	500	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

ITEM	NAME OF PART	MATERIAL	NOTES
5	Clapboard	PA66	UL94V-0
4	Spring	Stainless steel	/
3	Pin header	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准/IEC Standard:	/	/	/
过压类别/Overvoltage Category/污秽等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	/	1000/17	/
工频耐压/Withstanding Voltage(V/1Min)	/	AC3500	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	0.2~2.5/28~12	10.0/N=02~12P	5~6
剥线长度/Stripping length(mm)	-40~+105	Yes	Yes
使用温度范围/Operating temperature(°C)	-40~+105	Yes	Yes
符合RoHS标准/Conform to RoHS	Yes	Yes	Yes

MATERIAL: / SURFACE: /

MAT NO.: /  
 STATUS: /  
 APPD: Li GL 2020.06.10  
 CHKD: MGEK 2020.06.10

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**  
**DG245-10.0-XXP-1Y-00A(H)**

DRAWING NO.: DG245-10.0-C01  
 DRAFT: WangW 2020.06.10  
 TYPE: CUSTOMER DRAWING  
 SCALE: 2:1  
 SHEET: 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE