



公差等级/General	tolerance/(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	3	6	10	18	30	50	80	120	180	250	315	400	500	>500	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50	±Z	±Z

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	TYPE: CUSTOMER DRAWING	SCALE: 2:1	SHEET 1/1
MATERIAL: /		SURFACE: /		PANTONE / RAL PANTONE 7534U				
MAT NO.: /		NAME: <b>DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD</b>		8EDGRC-5.08-XXP-11-01A(H)				
STATUS: /		APPD: LanChH 2020.03.24		DRAWING NO.: 10001574				
CHKD: GongYzh 2020.03.24		DRT: CenSL 2020.03.24		REV T0				

ITEM	NAME OF PART	MATERIAL	NOTES
2	Pin header	Copper	Sn Plated
1	Housing	PA66	UL94V-0

UL 标准 / UL Standard:	B	C	D
额定电压/电涌 / Rated Voltage(V)/Current(A)	300/151	150/151	300/710
IEC 标准 / IEC Standard:			
额定电压/电涌 / Rated Voltage(V)/Current(A)			
过压类别 / Overvoltage Category / 污秽等级 / Pollution Degree	III / 3		
额定电压/电涌 / Rated Voltage(V)/Current(A)	320 / 20		
额定脉冲电压 (KV) / Rate Impulse Voltage (KV)	4		
额定扭矩 / Torque Tightening(N.m/Lb.in)	/		
线径范围 (裸线/带涂层) / Wire Range(rigid and flexible)(mm² /AWG)	/		
间距 / Pitch(mm) / 线径范围 / Poles	5.08 / N=02~24P		
剥线长度 / Stripping length(mm)	/		
使用温度范围 / Operating temperature(°C)	-40~+105		
符合 RoHS 标准 / Conform to RoHS	Yes		
标准颜色编号 / Standard color number:	PANTONE 7534U		

宁波高松电子有限公司  
NINGBO DEGSON ELECTRICAL CO., LTD

8EDGRC-5.08-XXP-11-01A(H)