



Pitch Range In mm		Nominal Dimension Range In mm				Tolerance				
Over	6	Over	10	Over	30	Over	100	Over	150	0.1/10
TO	10	TO	24	TO	60	TO	100	TO	150	±
6	10	±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2'

PCB LAYOUT

MATERIAL:	SURFACE: /											
MAT NO.:	/											
STATUS:	/											
APPD:	/											
CHKD:	/											
DRAFT: Zhangju	2020.05.26	DRAWING NO.:		DG38C-C01		TYPE:	CUSTOMER DRAWING		SCALE:	2:1		
REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	mm (inch)	NAME:	DG38C-A-XXP-1Y-00A(H)				
							DRAWING NO.:	DG38C-C01		REV	TO	
							TYPE:	CUSTOMER DRAWING		SHEET	1/1	

UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)	300/15	150/15	300/10
EC 标准/EC Standard:			
过压类别/Overvoltage Category/污染等			
级/ Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	300/24	300/24	600/24
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	5	5	5
额定扭矩/Torque Tightening(N·m/Lb.in)	M3, 0.5/4.43		
绞合范围/Wire Range(AWG)	22~14AWG		
间距/Pitch(mm)/绞合范围/Poles	8.25/N=02~24P		
剥线长度/Stripping Length(mm)	8		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

DEGSON® 宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD