



尺寸公差(mm)		0	>30	>60	>100	0.05/10
~	~	30	60	100	~	±T
±0.20	±0.30	±0.50	±0.70	±1.00	~	±T

Rated current	12A
Rated voltage	300V
Coil/Contact dielectric voltage	2500V/S
Dielectric voltage between contact	2500V/S
Screw torque	1.0Nm
External connection wire	20-14/0.5-2.5W
Ambient temperature	G/mm ²
Key controlled symbol	-40~+85℃
Conform to RoHS	*

Printing for laser marking/printing content is clear ,no broken line/rect
 Seal literal reference according to the foot position in the drawing

NO.	DESCRIPTION	MATERIAL NO.	QTY	MATERIAL	NOTES
1	DPKF08A-E3-00A(H)-N	300190000030	1		

MATERIAL: / SURFACE: /
 MAT.NO.: 300200000049

STATUS: /
 APPD: /
 CHKD: /

DRFT: /
 DRAWING NO.: 300000357

DESCRIPTION: **DEGSON**® NINGBO DEGSON ELECTRICAL CO., LTD
 DPKF08A-E3-00A(H)

TYPE: PRODUCT DRAWING SCALE: 1:1 SHEET 1/1

REV	ECN	DESCRIPTION	DRFT	DATE	SIZE: A4	mm	inch	TYPE: PRODUCT DRAWING	SCALE: 1:1	SHEET
										1/1