



公差/General Tolerances(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.45	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2

ITEM	NAME OF PART	MATERIAL	NOTES
4	Cover	PC	UL94V-2
3	Pin Header	Brass	Sn Plated
2	Screw	Steel	M4 N Plated
1	Housing	PA66+GF	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)	600/40	600/40	600/5
EC 标准/EC Standard:	过压类别/Overvoltage Category/污染等级/ Pollution Degree III/3 III/2 II/2		
额定电压/电流/Rated Voltage(V)/Current(A)	600/41	600/41	1000/41
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6	6	6
额定扭矩/Torque Tightening(N·m/Lb·in)	M4, 1.2/10.53		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.75~6/18~10		
间距/Pitch(mm)/线数范围/Poles	13.00/N=02~18P		
剥线长度/Stripping length(mm)	/		
使用温度范围/Operating temperature(°C)	-30~+120		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: / SURFACE: /

MAT NO.: / STATUS: /

APPD: / NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**

CHKD: / DRAWING NO.: **DG78H-E02**

DRAFTING R/J 2021.12.27 / TYPE: CUSTOMER DRAWING / SCALE: 1:1

REV	ECN	DESCRIPTION	DRAFT	DATE

