





未注公差/General tolerances(mm)													
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	~500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

0.1/10
±2'



ITEM	NAME OF PART	MATERIAL	NOTES
4	Cage	Steel	M5/Zn Plated
3	Current Carrier	Copper Alloy	Sn Plated
2	Screw	Steel	M5/Zn Plated
1	Housing	PA66	UL94V-0
UL 标准/UL Standard:		B	C
额定电压/电流/Rated Voltage(V)/Current(A)		600/85	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	/
额定电压/电流/Rated Voltage(V)/Current(A)		1000/76	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		8.0	/
螺丝扭矩/Torque Tightening(N·m/Lb.in)		M5, 3.0/27.0	
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)		1.0~16/16~4	
间距/Pitch(mm)		12.20	
剥线长度/Stripping length(mm)		13-14	
使用温度范围/Operating temperature(°C)		-40~+105	
符合RoHS环保要求/Conform to RoHS		Yes	
标准颜色编号/Standard color number: PANTONE / RAL		/	

MATERIAL:		SURFACE:	
MAT NO.:	/	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS:	/		
APPD:	Li GL 2020.04.03	NAME:	
CHKD:	Mao J 2020.04.03	PC16-01P-1Y-105A(H)	
DRFT:	XMY 2014.10.15	DRAWING NO.:	PC16-C14
REV	ECN	DESCRIPTION	DRFT
DATE	DATE	SIZE: A4	TYPE: CUSTOMER DRAWING
SCALE: 1:1		SHEET 1/1	

REV	ECN	DESCRIPTION	DRFT	DATE