

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、交还本文档的内容。侵犯者将承担赔偿责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。

FOR-1754 Rev.1.2

2



3


4

5

6

Dimensional tolerance(mm)					Length tolerance(mm)				 0.10/10 
0	>30	>60	>100		0	5000	10000		
30	60	100	150	>150	5000	10000	30000	>30000	
±0.25	±0.35	±0.55	±0.80	±1.10	±55	±105	±205	±505	
额定电压/Current /Rated Voltage/Current					1000V/70A				
绝缘电阻/Insulation resistance					≥100MΩ				
插拔次数/Mechanical working life(mating cycles)					100				
耐电压/Withstanding voltage					4250V DC				
使用温度范围/Operating temperature(°C)					-40~-+125°C				
防水等级/Levels of protection					IP67				
接线方式/Terminal					Crimp Termination				
线径/Wire range					8AWG/10mm ²				
剥线长度/Stripping length(mm)					8~9				
符合RoHS环保要求/Conform to RoHS					Yes				



MATERIAL: /		SURFACE: /	
MAT NO.:		 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS: /			
APPD:			
CHKD:			
DRFT: Luo XF 2022.06.02		NAME: ESS-70A-10-B/S-OR-00	
DRAWING NO.: /		REV	00
	SIZE: A4		TYPE: CUSTOMER DRAWING
SCALE: 1:1		SHEET	1/1

1

2

3

4

5

6