


Überblick

Informationen zum Produkt



Bus IO-DF750-200-11-2001A(H)-30050000139

Card type IO shell, 8 channel input output module Housing, with LED display, golden finger connector Disconnect all

Produktvorteile

- ☑ Free-hand plugging and unplugging, easy to assemble
- ☑ Internal bus through 6 gold-plated terminals at the bottom
- ☑ Equipped with 8 channels function module, each node is equipped with LED
- ☑ Two internal gold-plated blade connectors are used for power cascade expansion
- ☑ Can be installed on DIN rail

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

□

Dimension

length	100mm
width	12mm (main module)
Height	66.8mm

Mechanical parameters

structure type	Compact terminal module housing with signal LED
Material	PC+PA66
installation	DIN35 rail
Side by side installation	Dovetail groove clamping
label	Laser screen printing

color	C1 gray
-------	---------

Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

Connection method(IO)

wiring	Spring type wiring technology
Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

Zubehör

Accessories

IO housing	DF750-001-11-2001A(H)
------------	-----------------------

Die Geschäftsdaten

Nummer der Bestellung	30050000139
Verpackung Einheit	200
Minimale Bestellmenge	200
Produktgewicht (ohne Verpackung)	40