

Überblick

Informationen zum Produkt



Bus IO-DF750-002-11-2001A(H)-30050000130

Card type IO shell,can be equipped with RJ45 connector,LED indicator

Produktvorteile

- ☒ Dual network port with light RJ45 interface
- ☒ 8-bit address interface
- ☒ Internal bus through 6 gold-plated terminals at the bottom
- ☒ Equipped with 8 channels power module, each node is equipped with LED
- ☒ Two internal gold-plated blade connectors are used for power cascade expansion
- ☒ Can be installed on DIN rail

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

□

Dimension

length	93.5mm
width	48mm
Height	69mm

Mechanical parameters

structure type	Compact terminal module housing with signal LED
Material	PC+PA66
installation	DIN35 rail
Side by side installation	Dovetail groove clamping

label	Laser screen printing
color	C1 gray

Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

Connection method(IO)

wiring	Spring type wiring technology
Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm ²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

Zubehör

Accessories

IO housing	DF750-200-11-2001A(H)
------------	-----------------------

Die Geschäftsdaten

Nummer der Bestellung	30050000130
Verpackung Einheit	20
Minimale Bestellmenge	20
Produktgewicht (ohne Verpackung)	122.5

