

Überblick

Informationen zum Produkt



Interface module-DM50-IDC-34-40-4M-00A(H)-30040000093

Mitsubishi PLC dedicated, with indicator light, with screw connector and IDC stitching line, can be installed on DIN35 rail, 40 positions

Produktvorteile

The signal is clearly marked and the wiring is simple
Screw connection

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

□

Dimension

length	111mm
width	57mm
Height	44mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	32
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	40
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	34
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Zubehör

Accessories

Wire harness

DX210-4S-500-00A(H)

Die Geschäftsdaten

Nummer der Bestellung	30040000093
Verpackung Einheit	1
Minimale Bestellmenge	10
Produktgewicht (ohne Verpackung)	128