

Überblick

Informationen zum Produkt



16A-SM-2.5-92116900086

16A silver plating male pins, Adapter wire specification 2.5mm²

Produktvorteile

- ☒ High-precision turning process, stable and reliable products;
- ☒ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ☒ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

□

Marking

classification	Contact
Series	16A
Contact type	Crimping contact

versions

Female/Male	Male
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Material	Copper alloy
Plating material	Silver plated

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections (mm²)	2.5mm²
Conductor cross sections(AWG)	14AWG
Working current	≤16A
Contact resistance	≤1mΩ
Plating Thickness	≥2μm
Temperature range	-40℃~+125℃
Strip length	7.5mm
working life-mating cycles	≥500

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	92116900086
Verpackung Einheit	
Minimale Bestellmenge	100
Produktgewicht (ohne Verpackung)	1.57