

Überblick

Informationen zum Produkt



D32A-SF-2L-M25-21010000598

32A Lower base,double button,back cover ,side entry,M25 Thread hole

Produktvorteile

- ☑ Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ☑ Various installation methods and outlet directions to meet on-site wiring requirements;
- ☑ Snap-in combination structure, dustproof, waterproof, easy operation;

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

□

Marking

classification	Upper Housing/base
Series	A
Type	Surface mount base
Specification	Low structure

versions

Dimension	32A
locking Category	Double lock
Thread specification	1x M25

Material characteristics

Flammability rating	V-0
RoHS	conform
Material (upper housing/base)	Die-cast aluminium alloy
Material(upper housing/base)	spray
Color (upper housing/base)	Grey (RAL 7037)
Material (seal)	NBR
Material (lock catch)	Zinc plated

Technical specification

Limiting temperatures	-40℃~+125℃
IP class	IP65

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	21010000598
Verpackung Einheit	
Minimale Bestellmenge	1
Produktgewicht (ohne Verpackung)	443