

Überblick

Informationen zum Produkt



DQ-012-MC-21020000091

Heavy-duty insert, Number of contacts: 12+PE, Dimension: 3A, Rated voltage :400V, Rated current: 10A, Male insert, Crimping connector

Produktvorteile

- ✓Crimping connection technology, high wiring efficiency
- ✓Suitable for vibration occasions;
- ✓The wiring harness can be pre-installed;
- ✓Choose contacts with different wire diameters and coatings;
- ✓High-density pins, saving installation space;
- ✓With grounding protection.

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Marking

classification	Insert
Series	DQ

versions

Connection method	Crimping connection
Female/Male	Male
Dimension	3A
Number of positions	12

PE Contacts	Yes
-------------	-----

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated/gold plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	10A
	400V
Rated pulse voltage	6KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	7.5mm
Conductor cross sections (mm²)	0.14-2.5mm²
Conductor cross sections(AWG)	26-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accessories

Crimping tool|Removal tool

/

Die Geschäftsdaten

Nummer der Bestellung	21020000091
Verpackung Einheit	
Minimale Bestellmenge	5
Produktgewicht (ohne Verpackung)	23