

Überblick

Informationen zum Produkt



DA-004-FS-21020000102

Heavy-duty insert, Number of contacts: 4+PE, Dimension: 3A, Rated voltage : 400/230V, Rated current: 10A, Female insert, Cage clamp connector

Produktvorteile

- ☑ Spring cage connection technology, high vibration resistance;
- ☑ No special tools required, maintenance-free ;
- ☑ Less materials, easy to manage;
- ☑ With grounding protection.

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Marking

classification	Insert
Series	DA

versions

Connection method	Spring cage connection
Female/Male	Female
Dimension	3A
Number of positions	4
PE Contacts	Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	10A
	400/230V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	9.0mm
Conductor cross sections (mm²)	0.5-2.5mm²
Conductor cross sections(AWG)	20-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Zubehör

Accessories

Screwdriver

/

Die Geschäftsdaten

Nummer der Bestellung	21020000102
Verpackung Einheit	
Minimale Bestellmenge	5
Produktgewicht (ohne Verpackung)	15.33