


## Überblick

### Informationen zum Produkt



### DCKKB2.5-11020000073

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 500 V, Rated current: 24 A, Number of connectors: 4, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 28 - 12, Width: 5.1 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

### Produktvorteile

- ☑ Steel screw connection technology, reliable connection;
- ☑ Equipped with dual-channel bridge wells, circuit connection testing is more flexible;
- ☑ Unique plug-in bridge, high circuit connection efficiency;
- ☑ The box has a baffle to prevent mis-insertion;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

### Zertifizierung von Produkten



## Technische Daten

### Produktzeichnung

### 3D-Modell



### Overview

|                                           |                  |
|-------------------------------------------|------------------|
| Connection method                         | screw connection |
| Number of rows                            | 2                |
| number of connections                     | 4                |
| Open-end side panels                      | Yes              |
| Insulation Materials                      | PA               |
| Flame retardant grade, in line with UL 94 | V0               |

### Dimension

|                  |        |
|------------------|--------|
| NS 35/7,5 Height | 63mm   |
| End plate width  | 1.5mm  |
| NS 35/15 Height  | 70.5mm |
| length           | 76mm   |
| width            | 5.1mm  |
| Height           | 61.8mm |

#### Wiring data

|                                                                |                        |
|----------------------------------------------------------------|------------------------|
| Screw type                                                     | Slotted screw          |
| Conductor cross section flexible (ferrule with plastic sleeve) | 0.5-1.5mm <sup>2</sup> |
| Strip length                                                   | 8~9mm                  |
| Conductor cross section solid                                  | 0.2~4mm <sup>2</sup>   |
| Conductor cross section flexible                               | 0.2~2.5mm <sup>2</sup> |
| Conductor cross section solid AWG                              | 28~12                  |
| screw thread                                                   | M2.5                   |
| Tightening torque                                              | 0.4N.m                 |

#### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

#### IEC Electrical parameters

|                         |      |
|-------------------------|------|
| Rated voltage (III / 3) | 500V |
| Rated current (III / 3) | 24A  |
| Rated surge voltage     | 6KV  |

#### Environmental protection

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

RoHS

No excessive harmful substances

## Zubehör

## Marker

Top marker

/

Side marker

ZB5 / WB5

Marker support

/

## Accessories

Slotted screwdriver size (Blade thickness x Width)

0.6×3.5

Bridge

DFA2.5

End cover

D-DCKKB2.5

Partition plate

/

## Installation

End clamp

E-WS N / E-PC-1100A

Terminal strip marker support

KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2

DIN rail

NS35/7.5 &amp; NS35/15

## Marking &amp; Installation

Marking strip

ZB5

Marker cards

DBE-1

## Accessories

End cover

D-DCKKB2.5

Bridge

DFA2.5

End clamp

E-WS

DIN rail

NS35/7.5-1000-00A(H)

## Die Geschäftsdaten

|                                  |             |
|----------------------------------|-------------|
| Nummer der Bestellung            | 11020000073 |
| Verpackung Einheit               | 50          |
| Minimale Bestellmenge            | 50          |
| Produktgewicht (ohne Verpackung) | 11.64       |