

## Überblick

### Informationen zum Produkt



**DGFA2S-B1-24030000004**

Servo Connector plug plastic(bulk), Without cable, without ferrules terminal

### Produktvorteile

- ☑ Satisfy customers' harsh environment
- ☑ Save time for making wiring harness and improve work efficiency
- ☑ Compact design, Meet small motors needs

### Zertifizierung von Produkten



**RoHS**

**REACH**



## Technische Daten

### Produktzeichnung

### 3D-Modell

□

### Environmental conditions

Ambient temperature

-25°C...105°C

IP class

IP67

### General parameters

Rated current

7A

250V

Number of potentials

2

Insulation resistance

≥ 100 MΩ

Overvoltage level

II

Pollution level

2

|                   |       |
|-------------------|-------|
| Connection method | Crimp |
|-------------------|-------|

Material

|                                        |         |
|----------------------------------------|---------|
| Flammability rating ,in line with UL94 | V0      |
| Material contact surface               | Au      |
| Contact carrier material               | PA      |
| Sealing material                       | Silicon |

Zubehör

Die Geschäftsdaten

|                                  |             |
|----------------------------------|-------------|
| Nummer der Bestellung            | 24030000004 |
| Verpackung Einheit               | /           |
| Minimale Bestellmenge            | 100         |
| Produktgewicht (ohne Verpackung) | /           |