

Überblick

Informationen zum Produkt



FY-M12B-05F-M12B-05F-Q-0100-20030002028

M12B-Y distributor(PCB),Input terminal:Female,Output terminal1:Female,Output terminal2:Male

Produktvorteile

- ☑Single wire input, Multi wire output
- ☑Cost saving and convenient installation
- ☑Protection level:IP67/68
- ☑Widely used in industrial automation, rail transit and other industries

Zertifizierung von Produkten

RoHS REACH

Technische Daten

Produktzeichnung

3D-Modell

Environmental conditions

Ambient temperature

-25℃...85℃

IP class

IP67

General parameters

Rated current

4A

60V

Number of potentials

5

Insulation resistance

≥ 100 MΩ

Error-proof coding

B-Code

Overvoltage level	II
Pollution level	3
Insertion and pullout cycle	≥ 100

Material

Flammability rating ,in line with UL97	HB
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PU
Fixture body material	TPU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	20030002028
Verpackung Einheit	/
Minimale Bestellmenge	100
Produktgewicht (ohne Verpackung)	/