

Überblick

Informationen zum Produkt



FT-M12D-04F-M12D-04M-K4-0200-20030002032

M12D-T distributor(soldering), Input terminal:Female, Output terminal1:Male, Output terminal2:Female

Produktvorteile

- ☒ Single wire input, Multi wire output
- ☒ Cost saving and convenient installation
- ☒ Protection level:IP67/68
- ☒ Widely used in industrial automation, rail transit and other industries

Zertifizierung von Produkten

RoHS REACH

Technische Daten

Produktzeichnung

3D-Modell

Environmental conditions

Ambient temperature	-25℃...85℃
---------------------	------------

IP class	IP67
----------	------

General parameters

Rated current	4A
	250V
Number of potentials	4
Insulation resistance	≥ 100 MΩ
Error-proof coding	D-Code

Overvoltage level	II
Pollution level	3
Insertion and pullout cycle	≥ 100

Material

Flammability rating ,in line with UL97	HB
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PU
Fixture body material	TPU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	20030002032
Verpackung Einheit	/
Minimale Bestellmenge	100
Produktgewicht (ohne Verpackung)	/