

Überblick

Informationen zum Produkt



PB-M8A-03P-MM-SL7001-20020000016

Field mounted, Unshielded, Male, Straight, M8, Coding A, Screw connector, Cable
External cable diameter 4.0~6.0 mm

Produktvorteile

- ☑ Sealing optimization, protection level up to IP67
- ☑ Meet the harsh environment
- ☑ Miniature connector, Space saving
- ☑ Suitable for various occasions connection technology
- ☑ Compatible with the international and domestic same series products

Zertifizierung von Produkten



RoHS

REACH



Technische Daten

Produktzeichnung

3D-Modell

□

Dimension

Assembled cable outer diameter

4.0-6.0mm

Assembled conductor cross section

0.25~0.34 mm²

24~22 AWG

Environmental conditions

Ambient temperature

-40℃...85℃

IP class

IP67

General parameters

3A

Rated current	60V
Number of potentials	3
Insulation resistance	≥ 100 MΩ
Error-proof coding	A-Code
Overvoltage level	II
Pollution level	3
Connection method	Screw connection
Insertion and pullout cycle	≥ 100
Torque	0.3 Nm ... 0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-104
--------------------------	-----------------

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	20020000016
Verpackung Einheit	/
Minimale Bestellmenge	100
Produktgewicht (ohne Verpackung)	/

