

Überblick

Informationen zum Produkt



SD-M12A-04P-FF-SH8002-20030001081

Sensor/Actuator Female socket,M12,Coding A,Front panel installation/M16*1.5
Thread mounted,Soldering cup

Produktvorteile

- ☑ Sealing optimization, protection level up to IP68
- ☑ Meet the harsh environment
- ☑ Suitable for various occasions connection technology
- ☑ Compatible with the international and domestic same series products

Zertifizierung von Produkten



RoHS

REACH



Technische Daten

Produktzeichnung

3D-Modell

□

Environmental conditions

Ambient temperature

-40°C...105°C

IP class

IP68

General parameters

Rated current

4A

250V

Number of potentials

4

Insulation resistance

≥ 100 MΩ

Error-proof coding

A-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Installation in front of the board

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

Zubehör

Accessories

Sealing cap	CAP-M12-MP-8003
-------------	-----------------

Die Geschäftsdaten

Nummer der Bestellung	20030001081
Verpackung Einheit	/
Minimale Bestellmenge	100
Produktgewicht (ohne Verpackung)	/

