

## Überblick

### Informationen zum Produkt



**PMSH-M12B-05P-FF-SR8A01-20030001027**

Sensor/Actuator Cable,PVC,black,UL2517,Female plug,Angled,M12,Coding B,Shielded,Trimming cable end,Cable Cable length:1m

### Produktvorteile

- ☑ Sealing optimization, protection level up to IP68
- ☑ Meet the harsh environment
- ☑ Suitable for various occasions connection technology
- ☑ Compatible with the international and domestic same series products

### Zertifizierung von Produkten

**RoHS REACH**

## Technische Daten

### Produktzeichnung

### 3D-Modell

□

### Dimension

Cable length

1m

### Environmental conditions

Ambient temperature

-25℃...85℃

IP class

IP68

### General parameters

Rated current

4A

60V

Number of potentials

5

|                             |          |
|-----------------------------|----------|
| Insulation resistance       | ≥ 100 MΩ |
| Error-proof coding          | B-Code   |
| Overvoltage level           | II       |
| Pollution level             | 3        |
| Insertion and pullout cycle | ≥ 100    |
| Torque                      | 0.4 Nm   |

Material

|                                        |                           |
|----------------------------------------|---------------------------|
| Flammability rating ,in line with UL94 | V0                        |
| Contact material                       | CuZn                      |
| Material contact surface               | Au                        |
| Contact carrier material               | PA                        |
| Fixture body material                  | TPU                       |
| Coil material                          | Zinc alloy, nickel plated |
| Sealing material                       | Silicon                   |

Standards and specifications

|                          |                 |
|--------------------------|-----------------|
| Standards/specifications | IEC 61076-2-101 |
|--------------------------|-----------------|

Cable

|                                            |                                                |
|--------------------------------------------|------------------------------------------------|
| Cable type                                 | PVC Black                                      |
| Cable type(abbreviation)                   | PVC                                            |
| UL AWM form                                | UL2517                                         |
| Cross section                              | 0.34mm <sup>2</sup>                            |
| AWG signal wire                            | 22AWG                                          |
| Wire structure Signal wire                 | 17/0.16mm <sup>2</sup>                         |
| Core diameter (including insulation layer) | 1.30±0.05mm                                    |
| Wire color                                 | 1 Brown 2 White 3 Blue 4 Black 5 Gray knitting |

|                               |                                      |
|-------------------------------|--------------------------------------|
| Thickness, insulation         | 0.6mm                                |
| Cable outer diameter D        | 5.7 ±0.2mm                           |
| Outer sheath, material        | PVC                                  |
| Conductor insulation material | PVC                                  |
| Conductor material            | Tinned copper                        |
| Conductor resistance          | Maximum 59.4Ω/km (at 20 °C )         |
| Nominal cable voltage         | 300V                                 |
| Cable test voltage            | 2000V                                |
| Flame retardant               | Comply with UL 758/1581 FT1 standard |
| Halogen free                  | Yes                                  |

#### Zubehör

##### Accessories

Sealing cap

CAP-M12-MP-8001

#### Die Geschäftsdaten

|                                  |             |
|----------------------------------|-------------|
| Nummer der Bestellung            | 20030001027 |
| Verpackung Einheit               | /           |
| Minimale Bestellmenge            | 100         |
| Produktgewicht (ohne Verpackung) | /           |