


## Überblick

### Informationen zum Produkt



## DG24B-1-12060000163

Double-layer barrier terminal blocks, Rated current: 8A. Rated voltage (UL) : 300V, Cross section: 22~14AWG, pitch: 7.62mm, Color: gray, Contact surface: Tin

### Produktvorteile

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Used in industrial control field to save equipment installation space

### Zertifizierung von Produkten

## Technische Daten

### Produktzeichnung

### 3D-Modell

### Processing notes

Process

Wave soldering/manual soldering

### Connection capacity

AWG

22~14AWG

### Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

8A

Rated current (D)

8A

### Item properties

|                      |                              |
|----------------------|------------------------------|
| Type of installation | PCB welding                  |
| Pin arrangement      | Double-row of misalignment   |
| Connection method    | Screw connection             |
| Screwdriver          | slotted-phillips screwdriver |
| screw thread         | M3                           |
| Pitch                | 7.62mm                       |
| Number of potentials | 11                           |
| Pluggable or not     | Yes                          |
| Number of rows       | 2                            |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | Copper alloy              |
| Contact point metal surface | tin-plated                |
| Contact zone metal surface  | Gold plate                |
| Insulation Materials        | PBT                       |
| Insulating material group   | IIIa                      |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |        |
|--------------------|--------|
| Test Specification | UL1059 |
|--------------------|--------|

Environmental data

|                                 |             |
|---------------------------------|-------------|
| Ambient temperature (operation) | -40°C~125°C |
|---------------------------------|-------------|

Zubehör

Accessories

|  |  |
|--|--|
|  |  |
|--|--|

## Die Geschäftsdaten

|                                  |             |
|----------------------------------|-------------|
| Nummer der Bestellung            | 12060000163 |
| Verpackung Einheit               | 72          |
| Minimale Bestellmenge            | /           |
| Produktgewicht (ohne Verpackung) | 34.2        |