

## Überblick

### Informationen zum Produkt



### DG65S-A-12020000716

Single-layer PCB barrier terminal blocks, Rated current: 30A. Rated voltage (UL) : 300V, Cross section: 22~10AWG, pitch: 11.00mm, Color: black, Contact surface: Tin

### Produktvorteile

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Solder plate mounting for electrical connection of the device to the PCB

### Zertifizierung von Produkten



## Technische Daten

### Produktzeichnung

### 3D-Modell

□

### Processing notes

Process

Wave soldering/manual soldering

### Connection capacity

AWG

22~10AWG

Torque

1.2N.m

### Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

30A

|                   |     |
|-------------------|-----|
| Rated current (D) | 10A |
|-------------------|-----|

#### Electrical parameters IEC

|               |      |
|---------------|------|
| Rated current | 300V |
|               | 32A  |

#### Item properties

|                      |                               |
|----------------------|-------------------------------|
| Type of installation | PCB welding                   |
| Pin arrangement      | Single row in a straight line |
| Connection method    | Screw connection              |
| Screwdriver          | slotted-phillips screwdriver  |
| screw thread         | M4                            |
| Pitch                | 11mm                          |
| Number of potentials | 4                             |
| Pluggable or not     | no                            |
| Number of rows       | 1                             |

#### Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | Copper alloy              |
| Contact point metal surface | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

#### Mechanical tests

|                    |        |
|--------------------|--------|
| Test Specification | UL1059 |
|--------------------|--------|

#### Environmental data

|                                 |           |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~105℃ |
|---------------------------------|-----------|

## Zubehör

### Accessories

## Die Geschäftsdaten

|                                  |             |
|----------------------------------|-------------|
| Nummer der Bestellung            | 12020000716 |
| Verpackung Einheit               | 135         |
| Minimale Bestellmenge            | /           |
| Produktgewicht (ohne Verpackung) | 19.1        |