


Überblick

Informationen zum Produkt



DGR500-00A(H)-12010000271

Transfer barrier terminal blocks, Rated current: 500A. Rated voltage (UL) : 600V, Cross section: 300~750kcmil, pitch: 60mm, Color: black, Contact surface: Tin

Produktvorteile

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Provide the cabinet and panel electrical transfer connections

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	500A
Rated current (C)	500A

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line

Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M16
Pitch	60mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

Zubehör

Accessories

--	--

Die Geschäftsdaten

Nummer der Bestellung	12010000271
-----------------------	-------------

Verpackung Einheit	2
Minimale Bestellmenge	/
Produktgewicht (ohne Verpackung)	725