


## Überblick

### Informationen zum Produkt



## DGK12-111-13030000123

Building electronic housing ,length :53.6mm,DIN rail housing ,Upper housing with vent ,Can be used in distribution box comply with DIN 43880 standard , IP class:IP20.

### Produktvorteile

- ☒ Modern design
- ☒ flexible PCB connection
- ☒ high-efficiency DIN rail connector is optional
- ☒ Support Wall-mounted installation and distribution power box installation in accordance with DIN 43880 standards

### Zertifizierung von Produkten

## Technische Daten

### Produktzeichnung

### 3D-Modell

□

### Dimensions

|                                 |        |
|---------------------------------|--------|
| width                           | 53.6mm |
| length                          | 89.7mm |
| Height                          | 60.7mm |
| Depth from top edge of DIN rail | 54.7mm |

### PCB data

|                         |                                |
|-------------------------|--------------------------------|
| Number of PCB holders   | 15 (Upper cover 6+Base 9)      |
| PCB thickness           | 1.8mm                          |
| Installation location   | Vertical &horizontal(DIN rail) |
| PCBType of installation | Latching                       |

Item properties

|                           |                                                          |
|---------------------------|----------------------------------------------------------|
| IP class                  | IP20                                                     |
| Connection levels         | 1(Both sides)                                            |
| with ventilation openings | Yes                                                      |
| Maximum connection        | 32 (pitch: 2.5 mm); 20 (pitch: 5 mm); 12 (pitch: 7.5 mm) |

Material data

|                     |                                                 |
|---------------------|-------------------------------------------------|
| color               | Upper housing: light gray bottom housing: black |
| Material            | PC                                              |
| Flammability rating | V2                                              |

Environmental data

|                                           |                |
|-------------------------------------------|----------------|
| Ambient temperature (assembly)            | -5°C ~ +100°C  |
| Ambient temperature (operation)           | -40°C ~ +110°C |
| Ambient temperature (storage / transport) | -40°C ~ +70°C  |

Zubehör

Accessories

|  |  |
|--|--|
|  |  |
|--|--|

Die Geschäftsdaten

|                                  |             |
|----------------------------------|-------------|
| Nummer der Bestellung            | 13030000123 |
| Verpackung Einheit               | 10          |
| Minimale Bestellmenge            | 10          |
| Produktgewicht (ohne Verpackung) | 50          |