

Überblick

Informationen zum Produkt



MDR cable-DX220-3S-500-00A(H)-23040000070

MDR cable,connector1:MDR connector (1×20 Core,180° output) ,connector2:IDC/MIL female connector (1×20 Core,180° output)

Produktvorteile

- ☒ The cable is soft and has good bending resistance
- ☒ Prefabricated connector, beautiful appearance
- ☒ Provide single-ended and double-ended cables
- ☒ Suitable for servo position control mode
- ☒ Save wiring time, and can achieve fast wiring with the company's interface module

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

□

Overview

Single wire, number of twisted wires	20
Single stranded wire, material	Tinned copper
shield	Yes
Outer sheath, material	PVC
Outer sheath,color	black

Environmental data

Ambient temperature (operation)	-20 °C ... 80 °C
Ambient temperature (storage / transport)	-20 °C ... 80 °C

Standards/Regulations

Flame retardant	ULVW-1
Oil resistance	Oil resistant
Gasoline resistance	≤246Ω/KM
Connection meets standards	UL758

Technical data

Maximum allowable working voltage	30VDC
Maximum current carrying capacity of each path	0.7A
cable length	0.5米
Cable outer diameter	6.1mm
Single strand, cross-sectional area	0.08mm²
Single strand, cross section (AWG)	28

Connection data 1

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	20
spacing	1.27mm
Exit angle	180°

Connection data 2

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	20
Exit angle	180°
spacing	2.54mm

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	23040000070
Verpackung Einheit	1
Minimale Bestellmenge	10
Produktgewicht (ohne Verpackung)	50