

Überblick

Informationen zum Produkt



MIL cable-DX210-1DS-500-00A(H)-23040000004

MIL cable,connector1:IDC/MIL female connector (1×10 Core,180° output) ,connector2:multi-Core Cable

Produktvorteile

- ☒ The cable is soft and has good bending resistance
- ☒ Prefabricated connector, beautiful appearance
- ☒ Provide single-ended and double-ended cables
- ☒ Save wiring time, and can achieve fast wiring with the company's interface module

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

□

Overview

Single wire, number of twisted wires	10
Single stranded wire, material	Tinned copper
shield	Yes
Outer sheath, material	PVC
Outer sheath,color	black

Environmental data

Ambient temperature (operation)	-20 °C ... 80 °C
Ambient temperature (storage / transport)	-20 °C ... 80 °C

Standards/Regulations

Flame retardant	ULVW-1
Oil resistance	Oil resistant
Gasoline resistance	≤246Ω/KM
Connection meets standards	UL758

Technical data

Maximum allowable working voltage	30VDC
Maximum current carrying capacity of each path	0.7A
cable length	0.5米
Cable outer diameter	5.0mm
Single strand, cross-sectional area	0.08mm ²
Single strand, cross section (AWG)	28

Connection data 1

Connection name	Control system side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	10
spacing	2.54mm
Exit angle	180°

Connection data 2

Connection name	On-site side
Connection method	Multi-core wire
Connection volume	1
Number of digits	10
spacing	2.54mm

Zubehör

Die Geschäftsdaten	
Nummer der Bestellung	23040000004
Verpackung Einheit	1
Minimale Bestellmenge	10
Produktgewicht (ohne Verpackung)	50