

Überblick

Informationen zum Produkt

**TSCB4-10070000056**

Transformer terminal blocks, Rated current: 32A. Rated voltage
(III/2) : 800V, Color: Orange, Contact surface : Tin

Produktvorteile

- ✓ Screw connection technology, safe and reliable
- ✓ Rail installation method, suitable for transformer wiring

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell



Connection capacity

Conductor cross section solid	0.2~10mm ²
Conductor cross section flexible	0.2~10mm ²
AWG	24~6AWG
Torque	0.5N.m
Strip length	11mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V

Rated current (B)	30A
Rated current (D)	5A
Rated current (C)	30A

Electrical parameters IEC

Rated current	800V
	32A
Rated current(III/2)	800V
Rated surge voltage(III/2)	2.5KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Zubehör

Accessories

Coding strip	TZB4
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Die Geschäftsdaten

Nummer der Bestellung	10070000056
Verpackung Einheit	100
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	3.75