

Überblick

Informationen zum Produkt



DGP16-10090000016

Through-wall terminal blocks, Rated current: 76A. Rated voltage
(III/3) : 500V, Width: 12.1mm, Color: gray, Contact surface : Tin

Produktvorteile

- ☑ Screw connection technology, safe and reliable
- ☑ Through-wall installation, free positioning

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Connection capacity

Conductor cross section solid	0.5~16mm ²
Conductor cross section flexible	0.5~16mm ²
AWG	20~4AWG
Torque	2N.m
Strip length	16mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V

Rated current (B)	85A
Rated current (D)	5A
Rated current (C)	85A

Electrical parameters IEC

Rated current(III/3)	500V
Rated current	500V
	76A
Rated surge voltage(III/3)	6KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M5
Pitch	12.1mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Zubehör

Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

Die Geschäftsdaten

Nummer der Bestellung	10090000016
Verpackung Einheit	25
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	27