

Überblick

Informationen zum Produkt



DG332K-5.0-10040001252

Pluggable terminal blocks, Rated current: 12A, Rated voltage (III/2) 250V, Cross section: 1.5mm², pitch: 5.0mm, connector method: screw connector with wire protection, Color: green, Contact surface: Tin

Produktvorteile

- ☒ Fixed screw connection technology, safe and reliable
- ☒ Different poles can be combined through the side lock

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Connection capacity

Conductor cross section solid	0.2~1.5mm ²
Conductor cross section flexible	0.2~1.5mm ²
AWG	28~16AWG
Torque	0.4N.m
Strip length	6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	10A

Electrical parameters IEC

Rated voltage	250V
Rated current	12A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Connection direction	0°
Connection method	Screw connection with wire protection
Screwdriver	Slotted screwdriver
screw thread	M2.5
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Contact zone metal surface	Nickel plating
Insulation Materials	PBT
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-30℃~120℃
---------------------------------	-----------

Zubehör

Tool

Screwdriver	0.4x2.5mm, Slotted screwdriver
Operating tool	/

Accessories

Coding strip	/
Bridge	DG019-5.0
Marking strip	/
Others	/

Die Geschäftsdaten

Nummer der Bestellung	10040001252
Verpackung Einheit	#NA
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	#NA