

Überblick

Informationen zum Produkt



DG12HS-1.2-10080000039

Feed through terminal blocks, Rated current: 57A. Rated voltage
(III/2) : 750V, pitch: 11.5mm, Color: natural, Contact surface : Zn

Produktvorteile

- ☒ Can realize horizontal wire-to-wire connection
- ☒ Panel mounting, suitable for various situations

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

Connection capacity

Conductor cross section solid	1.5~10mm ²
Conductor cross section flexible	1.5~10mm ²
AWG	14~8AWG
Torque	0.8N.m
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	150V
Rated voltage (D)	300V

Rated current (B)	50A
Rated current (D)	10A
Rated current (C)	50A

Electrical parameters IEC

Rated current	750V
	57A
Rated current(III/2)	750V
Rated power frequency voltage(1min)	3KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3.5
Pitch	11.5mm
Number of potentials	12
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	steel
Contact point metal surface	Galvanized
Insulation Materials	PA66
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)

-40°C~105°C

Zubehör

Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

/

Tool

Operating tool

/

Screwdriver

/

Die Geschäftsdaten

Nummer der Bestellung

10080000039

Verpackung Einheit

65

Minimale Bestellmenge

Produktgewicht (ohne
Verpackung)

50