

Überblick

Informationen zum Produkt



DG107V-7.62-10040000809

PCB terminal blocks, Rated current: 32A, Rated voltage (III/2) 630V, Cross section: 0.5-6mm², pitch: 7.62mm, connector method: Front screw connector, Color: green, Contact surface : Tin

Produktvorteile

- ☒ Universal connection method to ensure a high degree of flexibility in device design
- ☒ Two solder pins reduce mechanical stress on solder joints
- ☒ Different poles can be combined through the side lock

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell



Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~6mm²

Conductor cross section flexible

0.5~6.0mm²

AWG

26~10AWG

Torque

0.5N.m

Strip length

13mm

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	30A

Electrical parameters IEC

Rated voltage	630V
Rated current(III/3)	500V
Rated current	32A
Rated current(III/2)	630V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	7.62mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper

Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Zubehör

Tool

Screwdriver	0.6x3.5mm, Slotted screwdriver
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Die Geschäftsdaten

Nummer der Bestellung	10040000809
Verpackung Einheit	315
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	16.984126984127

