

Überblick

Informationen zum Produkt



15EDGVHDM-3.5-10030005152

Pluggable terminal blocks, Rated current: 10A. Rated voltage
(III/2) : 125V, pitch: 3.5mm, Color: green, Contact surface : Tin

Produktvorteile

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ Multi-layer wire connection can achieve higher contact density

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

150V

Rated current (B)

10A

Rated current (C)

10A

Electrical parameters IEC

Rated voltage

250V

Rated current(III/3)

80V

Rated current

10A

Rated current(III/2)	125V
Rated current(II/2)	250V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Pitch	3.5mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Zubehör

Tool

Screwdriver

/

Operating tool

/

Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

15EDG-PWP

Die Geschäftsdaten

Nummer der Bestellung

10030005152

Verpackung Einheit

1620

Minimale Bestellmenge

Produktgewicht (ohne
Verpackung)

2.758