


## Überblick

### Informationen zum Produkt



**15EDGKRP-3.81-10010000814**

Pluggable terminal blocks, Rated current: 7A. Rated voltage  
( II / 2 ) : 250V, pitch: 3.81mm, Color: green, Contact surface : Tin

### Produktvorteile

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Keying requirements can be met
- ☒ Universal installation method, suitable for various situations

### Zertifizierung von Produkten



## Technische Daten

### Produktzeichnung

### 3D-Modell

### Connection capacity

|                                  |                         |
|----------------------------------|-------------------------|
| Conductor cross section solid    | 0.5~1.5mm <sup>2</sup>  |
| Conductor cross section flexible | 0.75~1.5mm <sup>2</sup> |
| AWG                              | 28~16AWG                |
| Torque                           | 0.2N.m                  |
| Strip length                     | 7mm                     |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated current (B) | 8A   |

### Electrical parameters IEC

|                           |       |
|---------------------------|-------|
| Rated voltage             | 250V  |
| Rated current             | 7A    |
| Rated current(II/2)       | 250V  |
| Rated surge voltage(II/2) | 2.5KV |

#### Item properties

|                      |                     |
|----------------------|---------------------|
| Connection direction | 0°                  |
| Connection method    | Screw connection    |
| Screwdriver          | Slotted screwdriver |
| screw thread         | M2                  |
| Pitch                | 3.81mm              |
| Number of potentials | 2                   |
| Pluggable or not     | Yes                 |
| Number of rows       | 1                   |

#### Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | tin-plated                |
| Contact zone metal surface  | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

#### Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

#### Environmental data

|                                 |           |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~105℃ |
|---------------------------------|-----------|

## Zubehör

### Tool

|             |                             |
|-------------|-----------------------------|
| Screwdriver | 0.4x2.5,Slotted screwdriver |
|-------------|-----------------------------|

|                |   |
|----------------|---|
| Operating tool | / |
|----------------|---|

### Accessories

|              |   |
|--------------|---|
| Coding strip | / |
|--------------|---|

|        |            |
|--------|------------|
| Bridge | DG032-3.81 |
|--------|------------|

|               |   |
|---------------|---|
| Marking strip | / |
|---------------|---|

|        |   |
|--------|---|
| Others | / |
|--------|---|

## Die Geschäftsdaten

|                       |             |
|-----------------------|-------------|
| Nummer der Bestellung | 10010000814 |
|-----------------------|-------------|

|                    |     |
|--------------------|-----|
| Verpackung Einheit | 200 |
|--------------------|-----|

|                       |  |
|-----------------------|--|
| Minimale Bestellmenge |  |
|-----------------------|--|

|                                  |      |
|----------------------------------|------|
| Produktgewicht (ohne Verpackung) | 2.32 |
|----------------------------------|------|