


Überblick

Informationen zum Produkt



15EDGKC-3.81-10010000669

Pluggable terminal blocks, Rated current: 8A. Rated voltage
(III/2) : 160V, pitch: 3.81mm, Color: green, Contact surface : Tin

Produktvorteile

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Keying requirements can be met
- ☒ Universal installation method, suitable for various situations

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

Connection capacity

Conductor cross section solid	0.5~1.5mm ²
Conductor cross section flexible	0.75~1.5mm ²
AWG	30~16AWG
Torque	0.2N.m
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	8A

Rated current (D)	8A
-------------------	----

Electrical parameters IEC

Rated voltage	160V
Rated current	8A
Rated current(III/2)	160V
Rated surge voltage(III/2)	2.5KV

Item properties

Connection direction	0°
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2
Pitch	3.81mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)

-40°C~105°C

Zubehör

Tool

Screwdriver

0.4x2.5,Slotted screwdriver

Operating tool

/

Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

/

Die Geschäftsdaten

Nummer der Bestellung

10010000669

Verpackung Einheit

200

Minimale Bestellmenge

Produktgewicht (ohne
Verpackung)

2.861