

Überblick

Informationen zum Produkt



SA-EBBH-2006-F-00A(H)-25080000002

Charging and discharging receptacle at the end of electric motorcycle battery, with rated current of 100A~120A; Rated voltage 72V DC; Withstand voltage 1500V AC; Insulation resistance > 500M Ω ; Protection grade: IP67 when mated &single.Mechanical life $\geq$ 3000 cycles; Pull out force > 20N; Working temperature: - 40 ~ 105 $^{\circ}$ C; Salt spray resistance for 72h; Flame retardant grade ul94-v0; Environmental protection:RoHS

Produktvorteile

- ☒ Compact structure and high space utilization
- ☒ Adopt bayonet locking structure to prevent accidental unlocking
- ☒ Direct plug operation, convenient and fast
- ☒ Signal pin No.: 0~8 pins
- ☒ Multiple auditory and visual feedback are inserted in place
- ☒ Beautiful appearance, fit human functional design

Zertifizierung von Produkten

RoHS

Technische Daten

Produktzeichnung

3D-Modell

☐

Marking

Series	DA
	DD
	DM

versions

Connection method	Crimping connection
Female/Male	Male

Dimension	3A
	32A
	6B
	10B
	24B
	32B
Number of positions	48B
	15
	25
	42

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	25080000002
Verpackung Einheit	
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	