

## Überblick

### Informationen zum Produkt



### RM-EBBH-2006-M-1000-00A(H)-250800000001

Charging and discharging plug at the end of electric motorcycle battery, with rated current of 100A~120A; Rated voltage 72V DC; Withstand voltage 1500V AC; Insulation resistance > 500M Ω; Protection grade: IP67 when mated; Mechanical life ≥ 3000 times; Pull out force > 20N; Working temperature: - 40 ~ 105 °C; Salt spray resistance for 72h; Flame retardant grade ul94-v0; Environmental protection:RoHS

### Produktvorteile

- ☑ Compact structure and high space utilization
- ☑ Adopt bayonet locking structure to prevent accidental unlocking
- ☑ Direct plug operation, convenient and fast
- ☑ Signal pin No.: 0~8 pins
- ☑ Multiple auditory and visual feedback are inserted in place
- ☑ Beautiful appearance, fit human functional design

### Zertifizierung von Produkten

# RoHS

## Technische Daten

### Produktzeichnung

### 3D-Modell

□

### Marking

|        |    |
|--------|----|
| Series | DA |
|        | DD |
|        | DF |

### versions

|                   |                     |
|-------------------|---------------------|
| Connection method | Crimping connection |
| Female/Male       | Male                |

|                     |     |
|---------------------|-----|
| Dimension           | 3A  |
|                     | 32A |
|                     | 6B  |
|                     | 10B |
|                     | 24B |
|                     | 32B |
| Number of positions | 48B |
|                     | 15  |
|                     | 25  |
|                     | 32  |
|                     | 42  |

Zubehör

#### Die Geschäftsdaten

|                                  |             |
|----------------------------------|-------------|
| Nummer der Bestellung            | 25080000001 |
| Verpackung Einheit               |             |
| Minimale Bestellmenge            |             |
| Produktgewicht (ohne Verpackung) |             |