

Überblick

Informationen zum Produkt



Bus IO-DF750-HT-200-11-1001A(H)-30050000227

Card IO housing, push-in structure, 16 aisle input and output module housing, with LED display, Gold finger connection is completely disconnected

Produktvorteile

- ☑ Hand-plugged, easy to assemble
- ☑ Internal bus through bottom 6 gold-plated terminals
- ☑ Equipped 16 channels functional module, LEDs per node
- ☑ Internal 2 gold-plated blade connectors for power cascading expansion
- ☑ Can be installed on DIN rail

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

□

Connection method (IO)

wiring

PUSH-IN wiring technology

Dimension

length

100mm

width

12mm (main module)

Height

66.8mm

Mechanical parameters

structure type

Compact terminal module housing with signal LED

Material

PC+PA66

installation	DIN35 rail
Side by side installation	Dovetail groove clamping
label	Laser screen printing
color	C1 gray

Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

Connection method(IO)

Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm ²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	30050000227
Verpackung Einheit	200 SKT
Minimale Bestellmenge	200 SKT
Produktgewicht (ohne Verpackung)	40g