

Überblick

Informationen zum Produkt



Relay base-DPTF08A-3-00A(H)-30020000053

DPTF relay base, used for 2PDT relay, screw connection

Produktvorteile

- ☑ Plug-in relay socket
- ☑ Safe isolation between coil and contacts
- ☑ 10A, 2PDT grade
- ☑ Arc partition between adjacent columns

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

□

Dimension

length	71mm
width	30mm
Depth including bracket	27.5mm

Environmental data

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage / transport)	-40~+65°C

Technical data

Rated voltage UN	300V
Rated current IN	10A

Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	30020000053
Verpackung Einheit	
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	