

Überblick

Informationen zum Produkt



DGB40-12010000463

Transfer Type, Rated voltage(UL): 600V, pitch: 40mm, Color: black, Contact surface: Tin

Produktvorteile

- ☒ Screw connection for worldwide use
- ☒ Screw connection for worldwide use
- ☒ Provide the cabinet and panel electrical transfer connections

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

□

Wiring capacity

torque

40N.m

Device properties

thread

M12

spacing

40mm

Electrical parameters UL

Rated voltage (B)

600V

Rated voltage (D)

600V

Item properties

Type of installation

panel

Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Hexagonal screwdriver
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40 °C ~125 °C
---------------------------------	----------------

Zubehör

Accessories

--	--

Die Geschäftsdaten

Nummer der Bestellung	12010000463
Verpackung Einheit	12
Minimale Bestellmenge	/
Produktgewicht (ohne Verpackung)	193.6

