


Überblick

Informationen zum Produkt



DG246-5.08-10060001891

Spring Type PCB Terminal Block,nominal current9A.Rated voltage(III/2):
320V,pitch:5.08mm,Color:green,Contact surface:Tin

Produktvorteile

- ☑PUSH-IN connection technology, fast wiring
- ☑Universal installation method, suitable for various situations

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~1.5mm²

Conductor cross section flexible

0.2~1.5mm²

AWG

26~16AWG

Strip length

10mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

10A

Rated current (D)	10A
-------------------	-----

Electrical parameters IEC

Rated voltage	320V
Rated current(III/3)	250V
Rated current	9A
Rated current(III/2)	320V
Rated current(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Push-in spring connection
Pitch	5.08mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Zubehör	
Accessories	
Screwdriver	/
Operating tool	/
Marker strip	/
other	/
Tool	
Wire take tool	/
Screwdriver	/

Die Geschäftsdaten	
Nummer der Bestellung	10060001891
Verpackung Einheit	480
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	5.434