

Überblick

Informationen zum Produkt



SA-EBBF-3005-F-25040000002

Female float connector for exchange battery. Rated current: 60A; Rated voltage: 72V DC; Withstand voltage: 1500V AC; Insulation resistance > 500M Ω ; Protection grade meet IP67 for female side only; Mechanical life $\geq$ 5000 times; Pull out force > 50N; Operating temperature: - 40 ~ 105 $^{\circ}\text{C}$; Salt spray resistance : 72h; Flame retardant grade: UL94-v0; Environmental protection: RoHS.

Produktvorteile

- ☒ The products are matched with each other and have the function of positive and negative insertion
- ☒ The floating amount when the product is inserted can compensate the gap between the vehicle body and the battery
- ☒ The guide post is aligned and inserted, which is convenient and fast

Zertifizierung von Produkten

RoHS

Technische Daten

Produktzeichnung

3D-Modell

□

Marking

Series

DA

DEE

DQ

DF

versions

Connection method

Spring cage connection

Female/Male

Male

Dimension	3A
	32A
	6B
	10B
	24B
	32B
Number of positions	48B
	20
	16
	18

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	25040000002
Verpackung Einheit	
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	