

## Überblick

### Informationen zum Produkt



## SA-EBBR-2006-F-25070000002

Rectangular socket with direct plug in and out .Rated current:50A; Rated voltage:110V DC; Withstand voltage:500V AC; Insulation resistance > 100M Ω; Protection grade meet IP67 for socket only; Mechanical life ≥ 3000 times; Pull out force > 30N; Operating temperature: - 40 ~ 105 ℃; Salt spray resistance : 72h; Flame retardant grade:UL94-v0; Environmental protection:RoHS.

### Produktvorteile

- ☑ Fast direct plug connection
- ☑ When the product is pulled out, the handle can be used to help unlock
- ☑ High plug life
- ☑ Beautiful appearance, more in line with human functional design

### Zertifizierung von Produkten

# RoHS

## Technische Daten

### Produktzeichnung

### 3D-Modell

□

### Marking

|                |        |
|----------------|--------|
| classification | Insert |
| Series         | DD     |
|                | DDD    |
|                | DM     |

### versions

|                   |                  |
|-------------------|------------------|
| Connection method | Screw connection |
|-------------------|------------------|

|                     |      |
|---------------------|------|
| Female/Male         | Male |
| Dimension           | 3A   |
|                     | 32A  |
|                     | 6B   |
|                     | 10B  |
|                     | 24B  |
|                     | 32B  |
| Number of positions | 48B  |
|                     | 14   |
|                     | 15   |

Zubehör

Die Geschäftsdaten

|                                  |             |
|----------------------------------|-------------|
| Nummer der Bestellung            | 25070000002 |
| Verpackung Einheit               |             |
| Minimale Bestellmenge            |             |
| Produktgewicht (ohne Verpackung) |             |