Überblick

Informationen zum Produkt

PM-EBS-0006-M-L300-25020000009

Male connector with direct plug in and out.Rated current:2A; Rated voltage:48V DC; Withstand voltage:300V AC; Insulation resistance ＞ 30M Ω; Protection grade meet IP66 when mated; Mechanical life ≥ 100 times; Pull out force ＞ 25N; Operating temperature: - 40 ~ 105 ℃; Salt spray resistance : 48h; Flame retardant grade:UL94-v0; Environmental protection:RoHS. Color: Insert insulation - black.

Produktvorteile

☑ Compact structure and high space utilization
☑Plug in error proofing, simple interface
☑ Direct plug operation, convenient and fast
☑The inner core insulator has different colors and is easy to identify
☑Beautiful appearance, more in line with human functional design

Zertifizierung von Produkten

RoHS

Technische Daten

Produktzeichnung

3D-Modell

Marking

Series	DD
	DK

versions

Connection method	Screw connection
Female/Male	Female
	16A

Dimension	6B
	10B
	16B
	24B
	48B
Number of positions	12

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	25020000009
Verpackung Einheit	
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	