

Überblick

Informationen zum Produkt



SM-EBS-0002-F-L300-25020000004

Female connector with direct plug in and out. Rated current: 2A; Rated voltage: 48V DC; Withstand voltage: 300V AC; Insulation resistance > 30M Ω ; Protection grade meet IP66 when mated; Mechanical life $\geq$ 100 times; Pull out force > 25N; Operating temperature: - 40 ~ 105 $^{\circ}\text{C}$; Salt spray resistance : 48h; Flame retardant grade: UL94-v0; Environmental protection: RoHS. Color: Insert insulation - red.

Produktvorteile

- ☒ Compact structure and high space utilization
- ☒ Plug in error proofing, simple interface
- ☒ Direct plug operation, convenient and fast
- ☒ The inner core insulator has different colors and is easy to identify
- ☒ Beautiful appearance, more in line with human functional design

Zertifizierung von Produkten

RoHS

Technische Daten

Produktzeichnung

3D-Modell

☐

Marking

Series

DD

DK

versions

Connection method

Screw connection

Female/Male

Female

16A

Dimension	6B
	10B
	16B
	24B
	48B
Number of positions	6

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	25020000004
Verpackung Einheit	
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	