

Überblick

Informationen zum Produkt



PM-EBS-0002-M-L300-25020000002

Male connector with direct plug in and out. Rated current: 2A; Rated voltage: 48V DC; Withstand voltage: 300V AC; Insulation resistance > 30M Ω; Protection grade meet IP66 when mated; Mechanical life ≥ 100 times; Pull out force > 25N; Operating temperature: - 40 ~ 105 °C; Salt spray resistance : 48h; Flame retardant grade: UL94-v0; Environmental protection: RoHS. Color: Insert insulation - red.

Produktvorteile

- ☑ Compact structure and high space utilization
- ☑ Plug in error proofing, simple interface
- ☑ Direct plug operation, convenient and fast
- ☑ The inner core insulator has different colors and is easy to identify
- ☑ Beautiful appearance, more in line with human functional design

Zertifizierung von Produkten

RoHS

Technische Daten

Produktzeichnung

3D-Modell

□

Marking

Series

DD

DK

versions

Connection method

Screw connection

Female/Male

Female

16A

Dimension	6B
	10B
	16B
	24B
	48B
Number of positions	6

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	25020000002
Verpackung Einheit	
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	