

Überblick

Informationen zum Produkt



SA-EBBM-2003-F-25060000002

Socket with direct plug in and out. Rated current: 20A; Rated voltage: 110V DC; Withstand voltage: 500V AC; Insulation resistance > 100M Ω ; Protection grade meet IP67 for socket only; Mechanical life $\geq$ 3000 times; Pull out force > 20N; Operating temperature: - 40 ~ 105 $^{\circ}\text{C}$; Salt spray resistance : 72h; Flame retardant grade: UL94-v0; Environmental protection: RoHS.

Produktvorteile

- ☒ Fast direct plug connection
- ☒ After plugging in place, it has auditory and visual feedback
- ☒ High plug life
- ☒ Beautiful appearance, more in line with human functional design

Zertifizierung von Produkten

RoHS

Technische Daten

Produktzeichnung

3D-Modell

□

Marking

classification	Insert
Series	DD
	DE
	DM

versions

Connection method	Crimping connection
Female/Male	Male

Dimension	3A
	10A
	6B
	10B
	16B
	24B
Number of positions	48B
	4
	2

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	25060000002
Verpackung Einheit	
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	