

Überblick

Informationen zum Produkt



RM-EBBL-2105-M-25050000002

Right angle plug with direct plug in and out, rated current:50A; Rated voltage:110V DC; Withstand voltage:500V AC; Insulation resistance > 100M Ω; Protection grade meet IP67 when mated; Mechanical life ≥ 3000 times; Pull out force > 25N; Operating temperature: - 40 ~ 105 °C; Salt spray resistance : 72h; Flame retardant grade:UL94-v0; Environmental protection:RoHS. Color: lock ring - blue.

Produktvorteile

- ☑ Fast direct plug connection
- ☑ After plugging in place, it has auditory and visual feedback
- ☑ High plug life
- ☑ Beautiful appearance, more in line with human functional design

Zertifizierung von Produkten

RoHS

Technische Daten

Produktzeichnung

3D-Modell

□

Marking

classification	Insert
Series	DD
	DDD
	DM

versions

Connection method	Screw connection
-------------------	------------------

Female/Male	Male
Dimension	3A
	32A
	1 module
	6B
	10B
	16B
	24B
	32B
Number of positions	48B
	3
	2
	1

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	25050000002
Verpackung Einheit	
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	